Shawver Well Company, Inc.
2700 Stanley Avenue
Fredericksburg, IA 50630

(563) 237-5341
(800) 568-4449

Location of Well

FLOYD, IA
T97-96N R17-16W

County Floyd
Township Floyd
Section
Quarters IN TOWN

Customer Information

CITY OF FLOYD

FLOYD, IA

Contact Date
Confirmation Date

Contact Information

Home Ph:
Work Ph:
Cell Ph:
Fax:

Best time to call:
Email:
Customer since:
Referred By:

Job Information

Area
T97-96N R17-16W
Latitude
Longitude
PWTS #
Permit Number

Confirmation
Start Date 8/1/1977
End Date 8/1/1977
Warranty Date
Warranty

Well Site Information

Actual Size
Depth
Elevation 1080
SWL
RPS
Max GPM

Air Lift
Exploratory -- To Ft
Mock Rock -- Acidize --
Well Use

Rig
Driller ; Cert #:
Driller 2

Pump Inst -- Liner--ft
Sulfide -- Screen--

Water Tests: Iron
PH
Nitrate

Made Water
Screen Size
Slot Size
Riser Pipe
Set From
Perforated From
Tail Pipe

Description:
The well is cased to 100' with 10" casing. The well is then cased from 125' to 200' with 8" casing.
Remarks:

Well Formation Log

From-To	Color	Formation
0' to 15'		Topsoil & yellow clay
15' to 33'		Blue clay
33' to 43'		Sand
43' to 100'		Limerock
100' to 178'		Limerock (Devonian)
178' to 191'		Shale
191' to 268'		Limerock (Silurian)
268' to 275'		Maquoketa shale

Bore Log

From-To — Bit Size - Number

Well Casing Log

From-To — Casing

Screen Size
Slot Size — Set From
Riser Pipe — Tail Pipe

Well Grout Used

Amount — Type

use for update

W-25143 City well

W-25143