

Well on Boyson Rd - N.
of I-390

Hiawatha

10/21/92

B. H. Bunker

Well #6
2030 Boyson Road

RECEIVED

NOV 02 1992

Kleitman Const. Inc.

240-245 Dol, lt o-g brn, m, sacc; large pieces show solution...
Cavities, fossils (common)

235-240 Dol, lt yel brn, f, large pieces, ^{slightly} Ca' corrou s.

230-235 Dol, lt yel brn, f.

225-230 " " " " " ⊕

220-225 " " " " " ⊕

215-220 " " " " " ⊕

210-215 Dol, dk yel brn, v.f; trace gr grn sh

205-210 " " " " " , dense

200-205 Dol, lt ol gr, f.

195-200 Dol, lt gr, dense → SL

190-195 Dol, lt gr → dk gr brn, dense → SL

185-190 " " " " " "

180-185 " " " " " Sandy

175-180 " " " " " "

170-175 " " " " " trace embedded sand.

165-170 Dol, dk yel brn, sub sacc → F

160-165 " " " " " "

155-160 " " " " " "

150-155 " " " " " "

145-150 " " " " " "

140-145 Dol, aa, mottled lt brn gr.

135-140 Dol, lt brn gr, v.f. - SL

130-135 Dol, lt gr, arg; Dol, aa.

125-130 Dol, lt brn ar. SL

Silurian

BERTMAN

OTIS

City of Hiawatha Department
of Public Works
2030 Boyson Road
Hiawatha, Iowa 52233
(319) 393-5555

Kenwood	120-125	Dol, lt. brn gr, SL
	115-120	" " " "
	110-115	" " " "
	105-110	Dol, lt gr, sandy, arg.
	100-105	Dol, dk. yel brn, F.
Spring Grove	95-100	" " " "
	90-95	" " " "
	85-90	" " " SL
	80-85	" " " "
	75-80	" " " "
Well	70-75	" " " F, fossil. l. fossils
	65-70	" " " "
	60-65	Clay
Pleistocene		

Hiawatha Water Department
 81 Emmons Street
 Hiawatha, Iowa 52256
 (712) 393-6553

WELL RECORD:

506 ft. deep
226 ft. of 18" Hole
280 ft. of 12" Hole
230 ft. of 12" Steel casing - cement grout
145 ft. pump setting
1,000 GPM 4,000-5,000 GPM on the bottom
12" finished hole size

Hiawatha Water Department
81 Emmons Street
Hiawatha, Iowa 52233
(319) 393-5556