

WELL			
DEPTH: 88'	DIAMETER: 16"	SWL: 31' 3"	CASING PT.:
LINER LOCATION:	PERFORATED: Yes No		
SCREEN LENGTH: 23'	SLOT SIZE:	LOCATION: 56'	TO:
Water Meter			
Yes or No:	Mfg:	Size:	Does it work:

PITLESS UNIT			
PITLESS MFG	Monitor	LENGTH	10'
PITLESS UPPER DIAM.	16"	PITLESS MODEL	
"O" RING SIZE	16"		
DROP PIPE CONNECTION DESCRIPTION:			
OTHER			
CHECK VALVE SIZE	8"	# OF	1
AIRLINE LENGTH	60'	AIRLINE MATERIAL	Toro
TRANSDUCER MANUFACTURER			
WALL HEIGHT OF BUILDING	Outside		
LAYBACK REQUIRED	N/A		
CLEAR VISION FOR OPERATOR THROUGH:	DOOR WINDOW	NONE	
ISOLATION VALVE TO PUMP TO WASTE:			
CONNECTION FOR PUMP-OFF:	Yes	TYPE: Fire Hydrant	SIZE:
DISTANCE TO DISCHARGE POINT: 20'			

SUGGEST WE CHANGE / PERFORM THE FOLLOWING:

WE CHANGED/PERFORMED THE FOLLOWING:

Altitude gauge

Airline

Discharge Gasket

"O" Rings

Sub Cable

Motor

Pump

Add Drop Pipe ____

Brush Well

Bail Well

Treat Well

Televise

CREW: John & Dan

COMMENTS: