

Shawver Well Company, Inc.

2700 Stanley Avenue
Fredericksburg IA 50630

96580

(563) 237-5341
(800) 568-4449

Location of Well				Well Details			
PWS - Well #2	County	Dubuque		Actual Size	7" Steel	Pump Inst	--
16991 Asbury Road	Township	Center		Depth	905'	Liner	-- ft
Dubuque, IA 52002	Section	15		SWL	515'	Screen	--
Latitude	Quarters	NESESE			640'		
Longitude	T&R			RFS	@ 60		
	Elevation	1140'		Air Lift		Acidize	-- gal
						Made Water	2 GPM @ 74'; 50 GPM @ 486'; 25 GPM @ 764'; 20 GPM @ 810'; 50 GPM @ 868'; 20 GPM @ 890'
Customer Information				Driller	Dave Halweg		
Sundown Mountain Resort				Driller Cert #	2814		
16991 Asbury Road				State Remarks			
Dubuque, IA 52002							
Job Information							
Job Use	Business						
PWIS #	PWSID#:	Start Date	08/24/2022				
Permit #	3126887	End Date	09/08/2022				
Formation Log				Bore Hole			
From-To	Color	Formation		From-To	Bit Size		
0 - 1	Yellow	Rock		0 - 19	12 1/4"		
1 - 5	Brown	Clay		19 - 722	10"		
5 - 20	Yellow - Orange	Limestone		722 - 905	6 1/4"		
20 - 74	Yellow	Limestone		Casing or Loops			
74 - 86	Gray	Limestone		From-To	Casing		
86 - 96	Blue - Green	Shale		+2 - 722	7" ODx .317 Steel		
96 - 118	Blue	Shale & Limestone - Creviced		Screen Details	Liner Details		
118 - 254	Blue - Green	Shale		Screen Size	Liner Size		
254 - 348	Brown	Shale		Slot Size	Set From		
348 - 362	Light Brown	Limestone		Set From	Perforated From		
362 - 486	Lt Brown - Yellow	Limestone		Riser Pipe			
486 - 564	Brown	Limestone		Tail Pipe			
564 - 637	Gray	Limestone & Shale		Grout Consumed			
637 - 669	Blue - Gray	Shale		Amount	Unit	Type	
669 - 695	White - Gray	Sandstone		12	Sk	EZ Seal	
695 - 700	Blue - Gray	Shale & Limestone		2	Sk	Holeplug	
700 - 722	Cream	Limestone		280	Sk	Neat Cement	
722 - 764	Tan	Limestone					
764 - 820	Tan - Red	Limestone - Green Streaks with Gray Shale					
820 - 860	Gray - Brown - Red	Limestone					
860 - 905	Brown	Limestone with Sandstone Streaks					